

BNZ Materials, Inc.

SAFETY DATA SHEET

Identification

Section 1.

GHS product identifie	r:	Marinite [®] A, Marinite [®] AHP
Other means Of identification:		None
Product type:		Calcium Silicate Board
SDS No.:		BNZ-20-102
Relevant identified use	es of the	substance or mixture and uses advised against:
Identified uses	:	Industrial heat processing and fire protection
Uses advised a	gainst:	
Supplier:		BNZ Materials, Inc. 6901 S. Pierce St., Suite 260 Littleton, CO 80128
		Technical Support: 800-955-8650 www.bnzmaterials.com
Emergency telephone Number:		TREC - 800-424-9300 or 703-741-5970 (Outside USA and Canada – calls accepted). 24 Hour service.
Section 2.		Hazards Identification
OSHA/HCS status :		aterial is considered hazardous by the OSHA Hazard Communication rd (29 CFR 1910.1200).
Classification of the substance or mixture:		INGENICITY - Category 1A FIC TARGET ORGAN TOXICITY (STOT) REPEATED EXPOSURE – Category 1 (Respiratory System)
	Eye Irr	ritant – Category 2 itant – Category 2B tage of the mixture consisting of ingredient(s) of unknown toxicity: 0%
<u>GHS label elements</u> Hazard pictograms :		
Signal word : Hazard statements :	Danger May ca	use cancer.

Revision Date: August 1, 2022

Precautionary statements

Prevention :	P201: Obtain special instructions before use.
	P202: Do not handle until all safety precautions have been read and understood.
	P264: Wash thoroughly after handling.
	P280: Wear protective gloves, protective clothing, eye protection, face protection
Response :	 P305+P351+P338: IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P308+P313: If exposed or concerned: Get medical advice/attention. P332+P313: If skin irritation occurs: Get medical advice/attention. P337+P313: If eye irritation persists: Get medical advice/attention. P352: If on skin: Wash with plenty of water. P362+P364: Take off contaminated clothing and wash before reuse.
Storage :	P405: Store locked up.
Disposal :	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplementary Information	Use precautions if exposure exceeds the established OSHA limits. This material does not present a hazard unless dust is generated from processing operations.
Hazards not otherw	vise

Classified

Section 3.

None known

Composition/Information on Ingredients

Substance or mixture: Mixture

Other means of: None identification

CAS number/other identifiersCAS number :MixtureProduct code :None

Ingredient name	CAS number	%
Calcium Silicate	1344-95-2	60 - 80
Calcium metasilicate (wollastonite)	13983-17-0	20 - 40
Man-made reinforcing fibers	None	0-10
Crystalline Silica (quartz)	14808-60-7	0.1 – 2

Any concentration shown as a range it to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4.	First Aid Measures
Description of neces	sary first aid measures
Inhalation:	Remove victim to fresh air. Drink plenty of water and blow nose to evacuate remaining dust. If coughing or irritation persist seek medical attention.
Eye contact:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Rinse for at least 15 minutes. If irritation persists seek medical attention.
Skin contact:	Gently wash with plenty of soap and water after each exposure. If skin becomes irritated and irritation persists seek medical attention.
Ingestion	If prolonged irritation to gastrointestinal tract or mouth persist seek medical attention.
	nptoms/effects, acute and delayed
Potential acute heal	<u>th effects</u>
Inhalation :	Respirable airborne particles may cause temporary irritation to the lungs and upper respiratory system.
Skin contact:	Prolonged exposure may cause dryness or irritation to the skin.
Eye contact:	Will cause mechanical irritation to the eyes. May cause moderate to severe eye irritation and dryness.
Ingestion:	May cause irritation to gastrointestinal tract or mouth.
Over-exposure signs	s/symptoms
Inhalation:	Adverse symptoms may include the following: Irritation, shortness of breath, chest pain
Eye contact:	Adverse symptoms may include the following: Irritation Dryness
Skin contact:	Adverse symptoms may include the following: Irritation Dryness
Ingestion:	Adverse symptoms may include the following: Irritation Stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician:	Medical conditions which may be aggravated by exposure include dry skin, dermatitis, and pre-existing lung conditions such as bronchitis, emphysema, and asthma. Cigarette smoking may increase the risk of silicosis, bronchitis, pneumoconiosis, and lung cancer in persons exposed to crystalline silica.
Specific treatments:	No specific treatment.
Protection of first-aiders:	No action shall be taken involving any personal risk or without suitable training Wear a suitable NIOSH-approved dust mask. Wash contaminated clothing before re-use.

Section 5.	Firefighting Measures

Specific hazards arising			
from the chemical:	None known other than those represented elsewhere in this SDS.		
Hazardous thermal decomposition produc	 Decomposition products may include the following materials: Calcium Silicates Crystalline Silica 		
Special protective acti	ons		
for firefighters	Material will not burn.		
_	Promptly isolate the scene by removing all persons from the vicinity of the		
	incident if there is a fire.		
	No action shall be taken involving any personal risk or without suitable training.		
	No special firefighting equipment is necessary.		
Special protective equipment for fire-fig	hters Firefighters should wear appropriate protective equipment and self- contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.		

Section 6.

Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

For non-emergency	
Personnel	No action shall be taken involving any personal risk or without suitable training.
	Evacuate surrounding areas.
	Keep unnecessary and unprotected personnel from entering.
	Do not touch or walk through spilled material.
	Provide adequate ventilation.
	Wear appropriate respirator when ventilation is inadequate.
	Put on appropriate personal protective equipment.

For emergency	
responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental	
precautions	Avoid dispersion of material and runoff and contact with soil, waterways, drains and sewers.
	This material does not pose a significant threat to the environment
Methods and mate	rials for containment and cleaning up
Small spill	Stop source of spill .
	Avoid creating airborne dust
	Use dust suppressant as necessary
	Place material into closed waste disposal container.
	Any sweeper or vacuum should be equipped with High Efficiency Particulate (HEPA) filter.
	Dispose of using a licensed waste disposal contractor.
Large spill	Stop source of spill.
	Avoid creating airborne dust
	Use dust suppressant as necessary
	Place material into closed waste disposal container.
	Any sweeper or vacuum should be equipped with High Efficiency Particulate (HEPA) filter.
	Dispose of using a licensed waste disposal contractor.
	Note: see Section 1 for emergency contact information and Section 13 for waste
	disposal.
Section 7.	Handling and Stanage
Section /.	Handling and Storage

Section 7.

Handling and Storage

Protective measures for safe handling

Protective Measures:	Calcium silicate boards do not present a hazard in their intact state. Minimize dust generation during cutting, milling, or grinding. Use appropriate respiratory protection if dust is present above the established exposure limits.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. During initial exposure to service temperatures, smoke may be emitted which can cause transitory irritation to the lungs and upper respiratory system.

Conditions for safe	storage,
including any	
incompatibilities	Store in accordance with local regulations.
	Store in original container protected from direct sunlight in a dry, cool and well-
	ventilated area, away from incompatible materials (see Section 10) and food and
	drink.

Section 8. Exposure Controls/Personal Protection

Control parameters

Occupational exposure limits:

US Occupational Safety and Health Administration Permissible Exposure Limit (OSHA PEL):

Irritant (Nuisance) Dust	
(all components except	
crystalline silica):	5 mg/m^3

Crystalline Silica	
Permissible Exposure Limit	$50 \ \mu g/m^{3}$
Action Level	$25 \mu g/m^3$

(See 29 CFR 1910.1053, effective June 23, 2018. Regulation contains additional requirements, including written exposure plan, medical exams, training, and recordkeeping.)

(See 29 CFR 1910.1000 Table Z-3)

American Conference of Governmental and Industrial Hygienists Threshold Limit Value (ACGIH TLV[®]):

Calcium silicate	10 mg/m ³
Calcium metasilicate (wollastonite)	3 mg/m^3
Crystalline Silica	0.025 mg/m ³

Note: TLV[®] and PEL values are for eight hour exposures, unless noted.

Appropriate

Engineering controls: If user operations generate dust, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Power equipment should be fitted with a properly designed dust collection device.

Environmental

Exposure controls:	Emissions from ventilation or work process equipment should be checked to
	ensure they comply with the requirements of environmental protection legislation.
	In some cases, fume scrubbers, filters or engineering modifications to the process
	equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene Measures:Wash hands, forearms and face thoroughly after handling chemical products,
before eating, smoking and using the lavatory and at the end of the working
period.
Appropriate techniques should be used to remove potentially contaminated
clothing.
Wash contaminated clothing before reusing.
Ensure that eyewash stations and safety showers are close to the workstation
location.

Skin Protection

Respiratory Protection:	Wear a NIOSH-approved dust mask to limit exposure to product dust. Higher dust levels may require use of a half or full mask respirator with dust filters. Use local exhaust if necessary to lower dust levels. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Eye/Face Protection:	Wear safety glasses with side shields or goggles complying with an approved standard to avoid exposure to dust.
Hand Protection:	Protective gloves should be worn when handling and to avoid abrasion or drying of skin.
Body Protection:	Personal protective equipment for the body should be selected based on the task being performed and the risks involved.

Other Skin Protection: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved.

Appearance
Physical State
Color
Odor
Odor Threshold
pН
Melting Point
Boiling Point
Flash Point
Burning Time

Solid boards and blocks of various size Off-white to gray None Not Applicable > 2300 °F (1260 °C) N/A None Not applicable

Specific Gravity	1.2 - 1.7
Burning Rate	Not applicable
Evaporation Rate	0 (butyl acetate = 1)
Flammability (solid, gas)	Not applicable
Lower Explosive (flammable) Limit	Not available
Upper Explosive (flammable) Limit	Not available
Vapor Pressure	Not applicable
Vapor Density	Not applicable
Relative Density	Not available
Solubility	Not available
Solubility in Water	Slight
Partition coefficient: n-octanol/water	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
SADT	Not available
Viscosity	Not available

Stability	and Reactivi	ty

Reactivity:	This product is normally not reactive.		
Chemical stability:	The product is stable under normal conditions of use.		
Possibility of Hazardous Reactions:	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.		
Conditions to Avoid:	Avoid strong acids and ammonium salts. Contact with strong oxidizing agents (such as fluorine, chlorine trifluroride) may present a fire hazard.		
Incompatible Materials:	Reactive or incompatible with the following materials: Hydrofluoric acid, fluorine, chlorine trifluoride, oxygen difluoride		

Hazardous Decomposition			
Products	Crystalline silica will dissolve in hydrofluoric acid and produce silicon tetrafluoride, a corrosive gas.		

Section 11. Toxicological Information

Information on toxicological effects

Acute toxicity

Section 10.

Product/ingredient name	Result	Species	Dose	Exposure

SAFETY DATA SHEET

None Knowe					
None Known					
Irritation/Corrosion: Not available					
Sensitization	Not available				
Mutagenicity	Not available				
Carcinogenicity:	Not available				
Reproductive toxicity	Not a	available			
Teratogenicity	Not available				
Specific target organ t	ovicit	¥7			
(single exposure)		y available			
G • 😷 4	• • .				
Specific target organ t		•	Swyotalling C	ilion which is loss	un to aques silisosis
(repeated exposure)			•		wn to cause silicosis. disease that is often fatal.
	Since	osis is a rapidly pro	gressive, no	n-cancerous rung (uisease that is often fatal.
Aspiration hazard	Not a	available			
Information on the lik	elv				
routes of exposure		es of entry anticipa	ted: Oral, D	ermal, Inhalation.	
Potential acute health	offoct	e -			
rotential acute nearth	enect	<u>.5</u>			
Inhalation :	Respirable airborne particles may cause temporary irritation to the lungs and upper respiratory system.				
Skin contact:	Prolonged exposure may cause dryness or irritation to the skin.				
Eye contact:	Will cause mechanical irritation to the eyes. May cause moderate to severe eye irritation and dryness.				
Ingestion:	May	cause irritation to	gastrointestii	nal tract or mouth.	
Symptoms related to t	he ph	ysical, chemical a	nd toxicolog	<u>ical characteristi</u>	<u>cs</u>
Inhalation:	Adverse symptoms may include the following: Irritation				
Eye contact:	Adverse symptoms may include the following: Irritation Dryness				
		-			
Skin contact:	Adve	erse symptoms may	include the	following:	

	Irritation Dryness	
Ingestion:	Irritation	ay include the following:
Delayed and immedia	Stomach pains ate effects and also chro	onic effects from short and long term exposure
<u>Short term exposure</u>		
Potential immediate effects:	Not available.	
Potential delayed effects :	Not available.	
Long term exposure		
Potential immediate effects:	Not available.	
Potential delayed effects :	Not available.	
Potential chronic hea effects:	l th Not available	
General:	No other known signif	icant effects or critical hazards.
Carcinogenicity:	Crystalline silica – long term overexposure may cause permanent and irreversible lung damage, including silicosis, and increase the risk of lung cancer, kidney, and liver damage. Silicosis is a rapidly progressive, non-cancerous lung disease that is often fatal.	
	nternational Agency	014808-60-7 Silica dust, crystalline, in the form
of for Rese a	arch on Cancer)	quartz or cristobalite - Group 1 (Sup 7, 68,100C, 2012)
	Toxicology Program eport on Carcinogens	Silica, Crystalline (Respirable Size) - Known To Be Human Carcinogen
OSHA:		Crystalline Silica classified as a Category 1A Carcinogen
Mutagenicity: Teratogenicity: Developmental: Fertility effects:	No known significant e No known significant e	effects or critical hazards. effects or critical hazards. effects or critical hazards. effects or critical hazards.
Numerical magazing	of toxicity	

<u>Numerical measures of toxicity</u> <u>Acute toxicity estimates</u>

Not available.

Section 12.	Ecological Information
Toxicity	Not available.
Persistence and Degradability:	Not available.
Bioaccumulative Potential:	Not available.
<u>Mobility in soil</u>	
Soil/water partition coefficient (K _{OC}):	Not available
Other adverse effects:	Most of the ingredients in this product are naturally occurring minerals, and, unless contaminated in service, are not hazardous to the environment.
Section 13.	Disposal Considerations
Disposal methods:	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14.	Transport Information			
	DOT	TDG Classification	IMDG	ΙΑΤΑ
	Classification			
UN Number	Not Regulated	Not Regulated	Not Regulated	Not Regulated

Special precautions for user:

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage

Section 15.

Regulatory Information

U.S. Federal regulations

TSCA 8(a) CDR Exempt/Partial exemption: Not applicable United States inventory (TSCA 8b): All components are listed.

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs): Not listed

Clean Air Act Section 602 Class I Substances: Not listed

Clean Air Act Section 602 Class II Substances: Not listed

DEA List I Chemicals (**Precursor Chemicals**): Not listed

DEA List II Chemicals (Essential Chemicals): Not listed

SARA 302/304 Composition/information on ingredients:

No components are listed.

SARA 304 RQ: Not applicable.

SARA 311/312 Classification :

Immediate (acute) Health Hazard	Delayed (chronic) Health Hazard	Fire Hazard	Reactivity Hazard	Sudden Release of Pressure
Yes	Yes	No	No	No

Section 313 listed: No Listed material/compound: Not Applicable

State regulations

New York:	Crystalline Silica
New Jersey:	Crystalline Silica
Pennsylvania:	Crystalline Silica
Massachusetts:	Crystalline Silica
Rhode Island:	Crystalline Silica

California Prop. 65: This product contains the following substances known to the State of California to cause cancer: Crystalline silica

International Lists

DSL (Canada)	All ingredients are listed, or exempt from inclusion, on the Canadian
	Domestic Substances List (DSL).

WHMIS 2015 (Canada):	See Section 2
Australia inventory (AICS):	Not determined.
China inventory (IECSC):	Not determined.
Japan inventory:	Not determined.
Korea inventory:	Not determined.
Malaysia Inventory (EHS Register):	Not determined.
New Zealand Inventory of Chemicals (NZIoC):	Not determined.
Philippines inventory (PICCS):	Not determined.
Taiwan inventory (CSNN):	Not determined.

Chemical Weapons Convention List Schedule I Chemicals: Not listed Chemical Weapons Convention List Schedule II Chemicals: Not listed Chemical Weapons Convention List Schedule III Chemicals: Not listed

DSCL (Europe): R48/20: Harmful – Danger of serious damage to health by prolonged exposure through inhalation. R36: Irritating to the eyes R39: Danger of serious irreversible side effects. R45: May cause cancer.

Section 16.

Other Information

Hazardous Material Information System (U.S.A.)

Health	1
Flammability	0
Physical Hazards	0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

<u>DISCLAIMER</u> – BNZ Materials, Inc., (BNZ) believes the information contained in this Safety Data Sheet (SDS) to be accurate and reliable as of the date of issue, and is provided in good faith as a service to our customers and to comply with applicable laws. This document is intended as a guide for the safe handling, storage, and use of this material under normal conditions of use. No representation, warranty, or guarantee, either express or implied, is intended or given. BNZ does not accept any liability for any loss, injury, or damage resulting from the use of this product.

History

Date of issue/Date of revision: Date of previous issue: Changes : Prepared by: August 1, 2022 November 7, 2018 Routine review and update; no significant changes T Square Associates, Inc. www.tsquare.us